

HTM Pro - T Series

Air Handling Unit



HTM 03-01 Compliant Cabinet Air Handling Unit
Compact, Compliant, Carbon-Saving

HTM-Pro

HTM-Pro is Daikin's cabinet-style AHU for modern healthcare settings. Compact yet powerful, it meets HTM 03-01 requirements and suits refurbishments, modular builds, and space-limited plant rooms. Installation is simplified while maintaining high standards for filtration, airflow, and hygiene- delivering compliance and peace of mind in critical care.

IAQ Matters

Delivers hospital-grade air quality with high-efficiency filtration and optimised airflow, supporting infection control, compliance, and well-being.

Compact Compliance Without Compromise

Meeting HTM 03-01 within existing building layouts is a challenge. The HTM-Pro solves this by delivering full HTM compliance in a space-saving cabinet style format - well suited to refurbishments, modular builds, and plant rooms where space is limited. Installation is simplified with no compromise on filtration, airflow, or hygiene.

Made in Britain

Developed and manufactured in the North East of England, the HTM-Pro reflects Daikin's commitment to UK engineering and healthcare with locally built, high-performance solutions and reduced transport emissions



Air flow Capability


Available in a range of sizes suitable for various applications, including treatment rooms, isolation areas, clinical spaces, and general wards.

Configurable to meet specific airflow and pressure regime requirements as outlined in HTM 03-01.

Form Factor

Delivered as a fully assembled cabinet unit, ideal for restricted access and space. Rigid single-piece build improves strength, reduces leakage, and supports hygienic performance in line with healthcare requirements.

Widths from just 1100 mm - designed for restricted plant rooms and refurbishments



Tool free, removable slide drain trays, for faster, safer hygiene maintenance.



Side pipework exits keep a clear front face and installation flush to walls.



Pre-wired and factory tested plug-and-play digital controls for quick commissioning and reliable operation.



Top duct connections to reduce footprint. Widths from just 1100mm for 0.85 to 1.42m³/s airflow.



Built-in LED lighting for safe, easy inspection and servicing.



Flexibility to meet your needs



Filter

- ePM10 70% (M5) primary filter
- F7 (ePM1 55%) filter last in line
- ePM10 70% (M5) return filter

Control

- Plug and play controls for an easy and quick start-up and unit operation

Heat Exchanger

- High-efficiency counter flow plate
- Up to 80% of the thermal energy is recovered

Casing and Insulation

- T2 TB2 Thermal break construction
- 42mm double skin panel, mineral wool insulation
- Pre-painted internal and external panels
- Internal Parts: Stainless Steel

Damper

- Class 3, rolled aluminium, lever mechanism, plastic free
- Suitable for motorisation

Coil

- Water fog coil
- -5°C to 0°C

Coil

- Water cooling coil
- water re-heatcoil
- $10^{\circ}\Delta\text{T}$
- DX/Electric options

Fan

- EC Fans, motor class IE5
- Plug and socket for quick changeover

Drain Tray

- Slide removable
- Tool-free removal

Easy Maintenance

- All components removed with few and simple actions
- Hinged doors allow full access up and down stream of each component

HTM-Pro

main features

Controls and Functionality

- Free cooling and free heating management
- VRV DX direct expansion integration
- Programmable scheduling
- Temperature logic (supply, return, ambient)
- Preloaded control parameters
- Factory-tested plug-and-play

Monitoring and Safety


- Analogue filter pressure monitoring
- Shut-off dampers with pre-wired spring return actuators on all air inlets and outlets
- Integrated frost protection
- Easy maintenance

Control Interface & Connectivity

- User-friendly digital interface
- Local supervision with optional remote monitoring
- BMS integration via Modbus or BACnet
- Optional water valve control

Lighting and Power

- 24V IP67-rated internal LED lighting operated from a single switch
- Separate power supply for internal lighting and integrated service socket



Compact design



Fully HTM 03-01 compliant



High airflow performance

Plug and Play Control Systems

- Daikin's Digital Control Platform, ensures HTM 03-01 compliant control with 3 pre-programmable operating modes (On, Eco, and Boost) for quick setup and flexible operation.
- Dedicated key sensors such as pressure monitoring transducers, ensure accurate and reliable environmental control.
- All units with factory-integrated controls are fully wired, pre-programmed, tested, and HTM 03-01 compliant, ensuring consistent and reliable installation.
- The optimised internal layout enhances serviceability and installation efficiency.

Daikin on Site

active remote monitoring


What is Daikin on Site?

24/7 remote monitoring of AHUs and chillers enabling Daikin experts to remotely optimise and maintain performance

Lower lifetime cost

Energy and maintenance make up 85% of lifetime system costs. DoS can keep energy costs to a minimum:

1. Provide maximum efficiency and reliability.
2. Prevent downtime and major repairs.



Benefits and Value

Instant Alarm Notifications
Instant alerts prevent disruption and downtime


Customisable Dashboard
Display the metrics and information most relevant to your operations.

Monitor and control your plant from any location
Remote adjustments reduce site visits and downtime

Real-Time and Historical Data Trends

- Make informed decisions quickly
- Improve system efficiency
- Identify cost-saving opportunities

Predictive Analytics for Proactive Maintenance
Analytics and trend analysis predict faults early and reduce downtime



Datapoint trend analysis



Advanced Alarm Dashboard

Technical Data

HTM Professional	Model	Size 1	Size 2	Size 3	Size 4	Size 5
Airflow	m ³ /s	0.95	1.45	1.95	2.45	2.95
HE thermal efficiency	%	>73				
External static pressure	Pa	300				
Power input ¹	kW	1.66	2.48	3.35	4.41	5.22
SFPv ²	kW/m ³ /s	1.75	1.71	1.72	1.80	1.77
Electrical supply Main	Phase (Ph)	3+N+PE				
	Frequency (hz)	50				
	Voltage (V)	400				
	Full Load Current ³ (A)	20.40	20.20		34.80	
Electrical supply Auxiliary ⁴	Phase (ph)	1+N				
	Frequency (hz)	50				
	Voltage (V)	230				
	Full Load Current ³ (A)	18.70				
Unit dimensions	Width (mm)	1,100	1,500	1,900	2,040	2,300
	Height ⁵ (mm)	2,060			2,150	
	Legth ⁶ (mm)	3,740			4,100	

Total absorbed power input at nominal airflow and clean filter conditions | 2. SFP and nominal airflow, 300pa and clean filters | 3. Full potential current of fan and controls panel | 4. Auxiliary supply for lighting and service socket | 5. Height includes base and excludes dampers | 6. Length excludes coil pipework.



For Product, Service & Maintenance,
Rental and Spares enquiries:



0345 565 2700



www.daikinapplied.uk



www.daikinrentalsolutions.uk



Follow us:
www.linkedin.com/company/daikin-applied-uk-ltd/



Daikin Europe NV, participates in the Eurovent Certified Performance programme for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A participates in the Eurovent Certified performance programme for Liquid Chilling Packages, Hydronic Heat Pumps and Air handling Units. Check ongoing validity of certificate: www.eurovent-certification.com

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Applied (UK). Daikin Applied (UK) Ltd has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Applied (UK) Ltd explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication.



Daikin Applied (UK) Ltd is certified to ISO 9001 Quality Management System (QMS), ISO 14001 Environmental Management System (EMS), and ISO 45001 Occupational Health and Safety (OH&S) management systems. For the latest certificates, visit: www.daikinapplied.uk/documents-download

