



F-gas Regulation compliance check

Make sure your equipment is in line with the EU regulation



Reduce the environmental impact of your equipment

Since your HVAC-R equipment contains fluorinated greenhouse gases (F-gases) such as hydrofluorocarbons (HFCs), you must comply with a series of requirements adopted in the European Union to ensure emission prevention and containment; and hence reduce the environmental impact of refrigerants.

F-gas Regulation (EU) No 517/2014

- › Puts in place mandatory measures to reduce F-gas emissions in the EU.
- › One of these measures is the prevention of emissions of F-gases by conducting periodical checks, proper servicing and recovery of these gases at the end of the equipment's life.

AHUs

CHILLERS

PROJECTS

SERVICE

Keep your equipment running efficiently by avoiding potential leaks



Why conduct F-gas leak checks?

HVAC-R equipment that contains fluorinated greenhouse gases in quantities of 5 tonnes of CO₂ equivalent or more must be checked for F-gas leakage by certified personnel only.

During these checks, precautionary measures are taken to prevent leaks. In case a leak is detected, it is repaired without undue delay.

How often to conduct leak checks?

The frequency of your equipment's leak inspections depends on its F-gas charge size measured in CO₂ equivalents as shown in the table.

The installation of a leakage detection system is mandatory for equipment that contains 500 t CO₂ or more. The proper functioning of the system should be checked at least once every 12 months.

If the equipment has a leakage detection system, the required frequency of leak checks is reduced by half.

Leak checks frequency	Tonnes of CO ₂ equivalent	Refrigerant			
		R410A (Kg)	R407C (Kg)	R134a (Kg)	R32 (Kg)
12 months	5 ≤ t CO ₂ e < 50	2.4 – 24	2.8 – 28	3.5 – 35	7.4 – 74
6 months	50 ≤ t CO ₂ e < 500	24 – 240	28 – 280	35 – 350	74 – 740
3 months	t CO ₂ e ≥ 500	≥ 240	≥ 280	≥ 350	≥ 740

We manage your F-gas requirements so that you don't have to

All commercial, industrial and public sector organisations must comply with obligations under the government's environmental policy on F-Gas and Ozone-Depleting Substances.

Our certified technicians can help you carry out different tasks such as regular leak checks, installation of leakage detection systems and diligent on-site record keeping with supporting templates. As well as recovery and/or destruction of gases before the equipment is discarded.

You can also combine the required F-gas inspections with one of our service plans.



Flexible service & maintenance packages

- > ALL manufacturers HVAC equipment maintained
- > 24/7 Emergency call out service
- > 24 hour response times to call outs
- > Qualified HVAC engineers located nationally
- > On-site training for 'front line' service requirements
- > F-Gas registered
- > Remote monitoring via the web
- > Full spares availability & management

For more information email info@daikinappliedservice.uk or visit www.daikinappliedservice.uk

North
01670 566 208

South
01322 428 092

Midlands
01214 563 156

Spares
01670 566 243



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Applied Service. Daikin Applied Service has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Applied Service explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Applied Service Printed on non-chlorinated paper.

